

# PAX4™ Series



## Versatile, Four- and Six-Inch-Wide OEM Print Engines

### **PAX4™ print engines deliver superior performance and reliability.**

The 110PAX4 and 170PAX4 print engines are the performance leaders in mission-critical print-and-apply applications. With enhanced connectivity, including wireless and Ethernet, along with all-metal construction, PAX4 print engines deliver outstanding value, reliability, and durability.

### **Better than ever for high-volume needs**

With improved serviceability, faster first-label-out time, and a fully functional real-time clock, the PAX4 print engines deliver what it takes to make print-and-apply solutions super performers. European voltage requirements are now met with the 28V I/O option.

### **Real-time connectivity and control**

Reduce downtime and increase productivity. Through ZebraLink™, PAX4 print engines can send you instant status alert messages and give you Web-based centralised control, allowing you to troubleshoot quickly and keep production lines moving.



### **PAX4™ Series**

Designed for high-speed, high-throughput applications, both the 110PAX4 (for four-inch printing) and the 170PAX4 (for print widths up to six inches) are ideal for print-and-apply applications including:

- Mission-critical industrial applications
- High-volume product, carton, case, and pallet labelling
- Packaging with accurate time and date stamping

## **Get the most out of your Zebra, put genuine Zebra supplies in!**

Zebra offers a wide range of supplies for PAX4 printers, all made to a high standard and suitable for a variety of applications.

- Manufactured exclusively for Zebra printers
- Laboratory-tested for optimum performance
- Proven to minimise wear and tear on printheads

▶ **For more information, visit [www.zebra.com](http://www.zebra.com)**



# Specifications at a glance\*

## Standard Features

- Print methods: Thermal transfer or direct thermal
- Orientation: Right-hand or left-hand
- Industrial all-metal construction
- 10MB DRAM
- Standard 4MB non-volatile flash memory, (optional 64MB)
- Applicator interface
- Transmissive and reflective media sensors
- Multilingual backlit LCD
- Enhanced alert notification – monitors printhead condition
- ZebraLink™
- Multi-level Element Energy Equalizer™ (E3™) for superior print quality
- 32-bit 133MHz RISC processor
- Zebra printer driver for Microsoft® Windows® 3.X and Windows 95/98/NT/2000
- Real-time clock
- ZPL II® – Universal language for Zebra printers

## Printer specifications

### 110PAX4™:

#### Minimum Print Area

- Width: 13mm (0.5")
- Length with standard memory: 13mm (0.5")
- Length with backfeed: 13mm (0.5")
- Length without backfeed: 6.5mm (0.25")

#### Maximum Print Area

- Width: 104mm (4.1")
- Length with standard memory: 990mm (39")
- Maximum continuous media print length: 10MB memory: 2,540mm (100")

#### Resolutions

- 8 dots/mm (203dpi) or 12 dots/mm (300dpi)

#### Maximum Print Speed

- 305mm (12") per second (203dpi)
- 203mm (8") per second (300dpi)

#### Memory

- 10MB DRAM; 2MB non-volatile flash

### 170PAX4™:

#### Minimum Print Area

- Width: 76mm (3")
- Length with standard memory: 76mm (3")
- Length with backfeed: 76mm (3")
- Length without backfeed: 25.4mm (1")

#### Maximum Print Area

- Width: 168mm (6.6")
- Length with standard memory: 990mm (39")
- Maximum continuous media print length: 10MB memory: 3,810mm (150")

#### Resolutions

- 8 dots/mm (203dpi) or 12 dots/mm (300dpi)

#### Maximum Print Speed

- 305mm (12") per second (203dpi)
- 203mm (8") per second (300dpi)

#### Memory

- 10MB DRAM; 2MB non-volatile flash

## Media Characteristics

### Labels

#### Media Thickness (label and liner)

- 0.148mm (0.0055") to 0.254mm (0.010")

## Media Types

- Continuous, die-cut or black mark

For optimum print quality and print engine performance, use Genuine Zebra® Supplies.

### Ribbons

#### Max. Roll Size

- 101.6mm (4") O.D. on a 25.4mm (1") I.D. core

#### Standard Length

- 900m capacity

#### Ribbon Set-up

- Ribbon wound ink-side out

Ribbon is recommended to be at least as wide as media.

## Operating Characteristics

### Environment

- Operating Temp. 0°C (31°F) to 40°C (105°F)
- Storage Temp. -40°C (-40°F) to 71° C (160°F)
- Operating Humidity: 20% to 95% non-condensing R.H.
- Storage Humidity: 5% to 95% non-condensing R.H.

### Electrical

- Universal power supply with power-factor correction 90-264 VAC, 48-62Hz

### Connectivity

- High-speed bi-directional parallel interface, Centronics®-compatible
- High-speed serial interfaces: RS-232-C and RS-422 with DB-9F connector
- RS-485 multi-drop capability
- Configurable baud rate (110 to 57.6KB), parity, data bits, and stop bits
- Software (XON/XOFF) or hardware (DTR/DSR) communication handshake protocols
- Applicator interface with DB-15F connector

### Agency Approvals

- UL-60950 3rd edition, CAN/CSA-C22.2 No 60950-00 3rd edition, FCC part 15 – Class A, ICES-003, EN60950, EN55022-Class A, EN61000-6-2, VCCI, CCC

## Physical characteristics

### 110PAX4™:

Width: 245mm (9.6")  
Depth: 379mm (14.9")  
Height: 300mm (11.8")  
Weight: 15.6kg (34.5lbs)

### 170PAX4™:

Width: 245mm (9.6")  
Depth: 432mm (17")  
Height: 300mm (11.8")  
Weight: 16.1kg (35.5lbs)

## Fonts/Graphics/Symbologies

### Fonts and Character Sets

- Bitmap fonts A to H and GS symbols are expandable up to 10 times, height- and width- independent
- Smooth-scalable font Ø (CG Triumvirate™ Bold Condensed) is expandable dot-by-dot, height- and width- independent
- IBM® Code Page 850 International Characters
- Contains UFST® from Agfa Monotype Corporation

## Graphic Features

- Supports user-defined fonts and graphics – including custom logos

### Bar Code Symbologies

- Linear Bar Codes: Codabar, Code 11, Code 39, Code 93, Code128 with subsets A/B/C and UCC Case Codes, EAN-8, EAN-13, Industrial 2-of-5, Interleaved 2-of-5, ISBT-128, Logmars, MSI, Plessey, Postnet, RSS, Standard 2-of-5, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions
- 2-Dimensional: Codablock, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, RSS

## Options and Accessories

- PCMCIA cards
- CompactFlash® cards
- Linear PCMCIA cards available 8MB and 32MB
- ZebraNet® 10/100 PrintServer
- ZebraNet Wireless Print Server
- Firmware support for downloadable TrueType™ fonts
- PC memory card
- Additional fonts available
- 24-28V I/O applicator interface
- Unicode™: WGLA through Swiss 721
- XML Firmware option

## Media specification

### 110PAX4™:

Label and liner width:

16mm (0.625") to 114mm (4.5")

Ribbon width: 25.4mm (1") to 108mm (4.25")

### 170PAX4™:

Label and liner width:

76mm (3") to 180mm (7.1")

Ribbon width: 76mm (3") to 180mm (7.1")

## ZebraLink Solutions

### Software

ZebraDesigner™ Pro  
ZebraNet™ Bridge Enterprise  
ZebraNet Utilities v 7.0  
Zebra Universal Driver  
ZBI-Developer™

### Networking

ZebraNet 10/100 Print Server  
ZebraNet Wireless Print Server

### Firmware

**ZPL II®** – Universal language for Zebra printers. Simplifies label formatting and enables format compatibility with other Zebra printers.

**Web View** – Enables you to connect and control your bar code printer's Web interface using a common Web browser.

**Alert** – Printers equipped with ZebraNet print servers will notify you via any email-enabled, wired, or wireless device to minimize downtime.

**Add ZBI 2.0™** – Optional, powerful programming enhancement that lets Zebra printers run stand-alone applications, connect with peripherals, and more.

\*Specifications subject to change without notice.

©2008 ZIH Corp. Element Energy Equalizer, E3, ZBI-Developer™ ZBI 2.0, ZebraLink and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head, ZebraNet and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Microsoft and Windows are registered trademarks of Microsoft Corporation. Centronics is a registered trademark of Centronics Data Computer Corporation. CG Triumvirate is a trademark of Agfa Division, Miles Inc. IBM is a registered trademark of International Business Machines Corporation. UFST is a registered trademark of Agfa Monotype Corporation. CompactFlash is a registered trademark of SanDisk Corporation. TrueType is a trademark of Apple Computer, Inc. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners.



### Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom

Telephone: +44 (0)1628 556000 Fax: +44 (0)1628 556001 E-mail: mseurope@zebra.com Web: www.zebra.com

### Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East & Africa: Dubai, South Africa